

Create/edit a sensor left open thermostat energy saver rule

GoSafer Security Knowledge Base

This operational reference is organized for GoSafer Security customers and staff. Alarm.com product names are retained where required for technical accuracy.

Overview

A Sensor Left Open Energy Saver rule can adjust a thermostat's setpoint or mode if a door, window or other sensor is left open for a specified duration.

Platform	Customer Website
Content type	How-to / Configuration
Source last updated	2025-06-04

Procedure

To create a sensor left open energy saver rule using the GoSafer Security customer portal (powered by Alarm.com)

1. Log in to the GoSafer Security customer portal (powered by Alarm.com).

2. Click Automation.

Find the Sensor Left Open Energy Saver rule, and click Configure.

In When any of these sensors, click to select which sensors the rule is applied to.

Note: There is a limit of 32 sensors per Sensor Left Open Energy Saver rule.

In Is Left Open for this duration, use the dropdown menus and click to select the thermostat actions for the rule.

If applicable and desired, click to select Apply to all thermostats to apply the rule to all thermostats on the system.

To add notification recipients

1. Click Add.
2. Click to select the desired recipients from the Address Book, or add an unlisted recipient by clicking New.
3. Click Close to add selected recipients.
4. Verify the notification is configured with the correct settings.
5. Click Save.

Source and support

For GoSafer Security assistance, visit gosafersupport.com.

Original

Alarm.com

reference:

https://answers.alarm.com/Customer/Website_and_App/Home_Automation/Thermostats/Create_edit_a_sensor_left_open_thermostat_energy_saver_rule

Always verify safety, installation, compatibility, and current UI details against the original manufacturer documentation before operational use.

Revision #1

Created 2026-09-01 00:30:00 UTC by Jerdenn Calag

Updated 2026-09-01 00:30:00 UTC by Jerdenn Calag